便捷式洗眼仪-说明书

尺寸 A4(210*285mm)

材质:铜版纸,行标157g

1版,对折

CMYK : 100 95 40 0 RGB : 26 49 104 WEB : #1a3168

Pantone: 280C

CMYK :20 100 100 0 RGB : 200 22 29

WEB :#C8161D Pantone: 1788C

色值 CMYK:000100

MADE IN CHINA

TO AVOID DANGER OF SUFFOCATION, KEEP THIS PLASTIC BAG AND KATON.

BAG IN CRIBS, BEDS, CARRIAGES OR PLAYPENS.THIS BAG IS NOT A TOY.

WARNING: Cancer and Reproductive Harm
- www.P65Warnings.ca.gov

Mfd. for NorthSky Supply Inc.

✓! WARNING

封底 封面



OLYMPIA

USER INSTRUCTIONS

P2 p1

OLYMPIA Version number: 2025v1

Mfd. for NorthSky Supply Inc. The Woodlands, TX 77380

[Product Name] Portable Eyewash Station [Model No.] S9-1001 [Compliance of Product]

(E ANSI Z358.1-2014 (R2020) OSHA®

This self-contained 9-gallon gravity-flow eyewash unit is ideal for use in both indoor and outdoor environments where chemical hazards or air pollutants are present. The unit activates within one second and delivers 9 gallons (35 liters) of water over 10 minutes through ABS plastic spray heads. The unit features polyethylene carrying handles.

- Technical Parameter:
 Dimensions: 23" × 11" × 15"
 Gross Capacity: 9 gallons (35 liters)
 Functional Capacity: 8 gallons (30 liters)
 Package Dimensions: 23" × 12" × 15"

Usage Instructions:

- 1. All personnel must be trained in the proper use of emergency eyewash equipment.
- 2. Ensure water supply is sufficient to reach the marked position.
- 3. Pull down the eyewash basin to activate water flow.
- Hold eyelids open and roll eyeballs in the water flow.
 Push up the basin to stop the water flow. Seek medical attention immediately.

- Eyewash units must be inspected weekly.
 Inspection & Maintenance Requirements:
- · Verify proper water flow
- · Examine hose connecting reservoir and basin (remove unit from service if surface
- cracking is present)
- · Check water level
- Ensure reservoir is free of fungi, algae, or other foreign materials
 Drain, flush, and refill the eyewash with water meeting hygienic standards once every 90 days or as needed.

OLYMPIA

Version number: 2025v1

Mfd. for NorthSky Supply Inc. The Woodlands, TX 77380

Installation:

Step one:

Drilling 11mm diameter's holes on the hard wall, such as concrete walls.



Step two:

Aligning holes of the wall and the hanging board, and inserting 8mm expansion bolt into each hole, and then tightening the upper screw.



Step three:

Hanging the green handle on the hanging



Designer: Date: 20250217

Product Design Team